

TXGT 60

Artikelnummer: 520.19.1011.2

EAN: 5703347532474



Specifikationer

Min. Luftflöde [m ³ /h]	282
Min. Ljudeffekt [dB(A)]	52
Max. Luftflöde [m ³ /h]	487
Max. Ljudeffekt [dB(A)]	65
Manöverpanel	Touchpanel av glas
Material	Rostfri



Aftrækstilbehør

Namn	sifra	Pris
Carbon Flex Filter	535.46.1000.9	3 485,00 kr
Mini Plasmex	535.21.1500.9	6 965,00 kr
Thermex Plasmex® filter I - Runt	535.10.1000.9	10 440,00 kr
Spännband 8 60-215	815.16.8208.9	275,00 kr
Anslutningssats Ø 160 mm	830.51.2162.9	1 125,00 kr
flexslang. Ø 162 mm per meter	800.70.4162.9	405,00 kr
Slangsats Ø160 1,2 meter	800.70.6160.9	755,00 kr
Ljud- och kondensisolerad flexslang Ø 162 mm	810.16.5160.9	1 045,00 kr
Avgassats - ljud/kondensisolerad Ø162 mm	830.51.6162.9	2 045,00 kr
Återcirkulationsfilter	535.19.3600.9	360,00 kr

Thermex Link

Namn	sifra	Pris
Safemex spisvakt - 1 fas	536.06.1000.0	9 685,00 kr
Thermex Trigger Link-modul	536.99.1000.9	2 660,00 kr
Thermex Plasmex® Smart Link-modul	536.99.1150.9	5 010,00 kr