

## Decor 840 900 mm Rostfri

Artikelnummer: 528.23.8498.2

EAN: 5703347531507

A

### Specifikationer

Min. Luftsflöde [m <sup>3</sup> /h]	290
Min. Ljudeffekt [dB(A)]	54
Max. Luftsflöde [m <sup>3</sup> /h]	540
Max. Ljudeffekt [dB(A)]	66
Luftmängd - boost [m <sup>3</sup> /t]	750
Ljudeffekt boost [dB(A)]	70
Manöverpanel	Touchpanel av glas
Material	Rostfri



## Aftrækstilbehør

Namn	sifra	Pris
Thermex Plasmex® filter I - Runt	535.10.1000.9	10 440,00 kr
Mini Plasmex	535.21.1500.9	6 965,00 kr
flexslang, Ø 162 mm per meter	800.70.4162.9	405,00 kr
Carbon Flex Filter	535.46.1000.9	3 485,00 kr
Ljud- och kondensisolerad flexslang Ø 162 mm	810.16.5160.9	1 045,00 kr
Spännband 6 60-165 mm	815.16.8206.9	195,00 kr
Anslutningssats Ø 160 mm	830.51.2162.9	1 125,00 kr
Slangsats pvc ø162 mm	800.70.7160.9	1 005,00 kr
Slangsats Ø160 1,2 meter	800.70.6160.9	755,00 kr
Avgassats - ljud/kondensisolerad Ø162 mm	830.51.6162.9	2 045,00 kr

## Thermex Link

Namn	sifra	Pris
Thermex Trigger Link-modul	536.99.1000.9	2 660,00 kr
Prolink Basic II	536.99.1501.9	6 150,00 kr
Prolink Plasmex II	536.99.1503.9	16 085,00 kr
Prolink Premium II	536.99.1505.9	13 135,00 kr
Thermex Top Link Module II	536.99.1300.9	4 265,00 kr
Safemex spisvakt - 1 fas	536.06.1000.0	9 685,00 kr
Thermex Plasmex® Smart Link-modul	536.99.1150.9	5 010,00 kr